



IMPACT CASES INC. • 3455 - 14TH AVE., MARKHAM, ON L3R 0H4, CANADA
TEL 905-470-7888 / 800-881-7544 • FAX 905-470-7843 / 800-541-0765
WWW.CONQUESTCASES.COM / WWW.IMPACTCASES.COM

ENGINEERED FOR ANY DESTINATION

CASE SIZE MATRIX

CONQUEST • TARGET • STANDARD REFERENCE

CONQUEST™ RACKMOUNT — SHOCK-MOUNTED STD 19 IN.

Standard Size Matrix — every rack height ships in both E.I.A. hole patterns, all six payload classes and all five case colours.

RACK HEIGHT	HEIGHT (IN.)	E.I.A. HOLE PATTERNS	RACK DEPTHS AVAILABLE (IN.)	PART NUMBER PATTERN	NOTES
5U	8.75	STD (Round) SQ (Square)	24 30 36	CON-SR-5U[D]-[STD/SQ]-[X]-[COL]	—
7U	12.25	STD (Round) SQ (Square)	24 30 36	CON-SR-7U[D]-[STD/SQ]-[X]-[COL]	—
9U	15.75	STD (Round) SQ (Square)	24 30 36	CON-SR-9U[D]-[STD/SQ]-[X]-[COL]	—
12U	21.00	STD (Round) SQ (Square)	24 30 36	CON-SR-12U[D]-[STD/SQ]-[X]-[COL]	—
15U	26.25	STD (Round) SQ (Square)	24 30 36	CON-SR-15U[D]-[STD/SQ]-[X]-[COL]/LH	Add. Handles on Lids
18U	31.50	STD (Round) SQ (Square)	24 30 36	CON-SR-18U[D]-[STD/SQ]-[X]-[COL]/LH	Add. Handles on Lids
21U	36.75	STD (Round) SQ (Square)	30 36	CON-SR-21U[D]-[STD/SQ]-[X]-[COL]/LH	Add. Handles on Lids
26U	45.50	STD (Round) SQ (Square)	30 36	CON-SR-26U[D]-[STD/SQ]-[X]-[COL]/LH	Add. Handles on Lids
30U	52.50	STD (Round) SQ (Square)	30 36	CON-SR-30U[D]-[STD/SQ]-[X]-[COL]/LH	Add. Handles on Lids

RACK HEIGHT — CUSTOM SIZES AVAILABLE

The heights above are our standard reference range. ConQuest rackmount cases can be built in any U height from 4U to 42U to match your equipment — contact us for a custom quote outside this table.

PAYLOAD WEIGHT — REPLACE [X]

A	20 - 49 lbs. — Aluminum Rack
B	50 - 99 lbs. — Aluminum Rack
C	100 - 170 lbs. — Aluminum Rack
D	171 - 250 lbs. — Aluminum Rack
E	251 - 350 lbs. — Aluminum Rack
F	351 - 500 lbs. — Steel Rack

CASE COLOUR — REPLACE [COL]

BK	Textured Black
BL	Textured Blue
GR	Textured Green
RD	Textured Red
GT	Textured Graphite

For correct payload configuration in part number, replace "X" with the appropriate letter designation from the payload weight table. For correct colour configuration in part number, replace "COL" with the appropriate two-letter designation from the case colour table.