



IMPACT CASES INC. • 3455 - 14TH AVE., MARKHAM, ON L3R 0H4, CANADA
TEL 905-470-7888 / 800-881-7544 • FAX 905-470-7843 / 800-541-0765
WWW.CONQUESTCASES.COM / WWW.IMPACTCASES.COM

ENGINEERED FOR ANY DESTINATION

CASE SIZE MATRIX

CONQUEST™ SINGLE LID — STANDARD REFERENCE

CONQUEST™ SINGLE LID CASES — SIZE MATRIX

HL = Hinged-Lid • RL = Removable-Lid •
Highlighted rows = available stock to 15
business days (lead times may vary for other
sizes & configurations).

BASE PART NUMBER	SHELL THK (IN.)	LID STYLE	L (IN.)	W (IN.)	OVERALL H (IN.)	BASE D (IN.)	LID D (IN.)	APPROX. WT (LB)	RHW	RW	CA-F	CA-R	FL	LL	TD	HA	PH
CON-063-22X18X10(7.5+2.5)/HL/REC	0.063	HL	22	18	10	7.5	2.5	18.8	✓	—	—	—	—	✓	—	✓	✓
CON-063-22X18X12(9.5+2.5)/HL/REC	0.063	HL	22	18	12	9.5	2.5	19.8	✓	—	—	—	—	✓	—	✓	✓
CON-063-22X18X18(15.5+2.5)/HL/REC	0.063	HL	22	18	18	15.5	2.5	22.8	✓	—	—	—	—	✓	—	✓	✓
CON-063-24X12X12(9.5+2.5)/HL/REC	0.063	HL	24	12	12	9.5	2.5	17.4	✓	—	—	—	—	✓	—	✓	✓
CON-063-24X18X12(9.5+2.5)/HL/REC	0.063	HL	24	18	12	9.5	2.5	20.7	✓	—	—	—	—	✓	—	✓	✓
CON-063-24X18X14(11.5+2.5)/HL/REC	0.063	HL	24	18	14	11.5	2.5	21.8	✓	—	—	—	—	✓	—	✓	✓
CON-063-24X18X16(13.5+2.5)/HL/REC	0.063	HL	24	18	16	13.5	2.5	22.9	✓	—	—	—	—	✓	—	✓	✓
CON-063-24X18X18(15.5+2.5)/HL/REC	0.063	HL	24	18	18	15.5	2.5	23.9	✓	—	—	—	—	✓	—	✓	✓
CON-063-24X24X12(9.5+2.5)/HL/REC	0.063	HL	24	24	12	9.5	2.5	25.7	✓	—	✓	✓	—	✓	—	✓	✓
CON-063-24X24X18(15.5+2.5)/HL/REC	0.063	HL	24	24	18	15.5	2.5	29.3	✓	—	✓	✓	—	✓	—	✓	✓
CON-063-24X24X24(21.5+2.5)/HL/REC	0.063	HL	24	24	24	21.5	2.5	33.0	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X12X12(9.5+2.5)/HL/REC	0.090	HL	30	12	12	9.5	2.5	24.4	✓	—	—	—	—	✓	—	✓	✓
CON-090-30X18X12(9.5+2.5)/HL/REC	0.090	HL	30	18	12	9.5	2.5	29.5	✓	—	—	—	—	✓	—	✓	✓
CON-090-30X18X18(15.5+2.5)/HL/REC	0.090	HL	30	18	18	15.5	2.5	34.7	✓	—	—	—	—	✓	—	✓	✓
CON-090-30X24X12(9.5+2.5)/HL/REC	0.090	HL	30	24	12	9.5	2.5	36.2	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X24X16(13.5+2.5)/HL/REC	0.090	HL	30	24	16	13.5	2.5	40.1	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X24X18(15.5+2.5)/HL/REC	0.090	HL	30	24	18	15.5	2.5	42.1	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X24X24(21.5+2.5)/HL/REC	0.090	HL	30	24	24	21.5	2.5	47.9	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X30X12(9.5+2.5)/HL/REC	0.090	HL	30	30	12	9.5	2.5	43.0	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X30X18(15.5+2.5)/HL/REC	0.090	HL	30	30	18	15.5	2.5	49.6	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X30X24(21.5+2.5)/HL/REC	0.090	HL	30	30	24	21.5	2.5	56.1	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-30X30X30(26+4)/RL/REC	0.090	RL	30	30	30	26	4	67.2	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-36X12X12(9.5+2.5)/HL/REC	0.090	HL	36	12	12	9.5	2.5	28.5	✓	—	—	—	—	✓	—	✓	✓
CON-090-36X18X12(9.5+2.5)/HL/REC	0.090	HL	36	18	12	9.5	2.5	34.3	✓	—	—	—	—	✓	—	✓	✓
CON-090-36X18X18(15.5+2.5)/HL/REC	0.090	HL	36	18	18	15.5	2.5	40.1	✓	—	—	—	—	✓	—	✓	✓
CON-090-36X24X12(9.5+2.5)/HL/REC	0.090	HL	36	24	12	9.5	2.5	41.6	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-36X24X18(15.5+2.5)/HL/REC	0.090	HL	36	24	18	15.5	2.5	48.1	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-36X24X20(17.5+2.5)/HL/REC	0.090	HL	36	24	20	17.5	2.5	50.3	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-36X24X24(21.5+2.5)/HL/REC	0.090	HL	36	24	24	21.5	2.5	54.6	✓	—	✓	✓	—	✓	—	✓	✓
CON-090-36X30X12(9.5+2.5)/HL/REC	0.090	HL	36	30	12	9.5	2.5	49.1	✓	—	✓	✓	—	✓	—	✓	✓

	BASE PART NUMBER	SHELL THK (IN.)	LID STYLE	L (IN.)	W (IN.)	OVERALL H (IN.)	BASE D (IN.)	LID D (IN.)	APPROX. WT (LB)	RHW	RW	CA-F	CA-R	FL	LL	TD	HA	PH
	CON-090-36X30X18(15.5+2.5)/HL/REC	0.090	HL	36	30	18	15.5	2.5	56.2	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-36X30X24(21.5+2.5)/HL/REC	0.090	HL	36	30	24	21.5	2.5	63.4	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-36X30X30(26+4)/RL/REC	0.090	RL	36	30	30	26	4	75.8	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-36X36X12(9.5+2.5)/HL/REC	0.090	HL	36	36	12	9.5	2.5	54.8	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-36X36X18(15.5+2.5)/HL/REC	0.090	HL	36	36	18	15.5	2.5	62.6	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-36X36X24(21.5+2.5)/HL/REC	0.090	HL	36	36	24	21.5	2.5	70.5	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-36X36X30(26+4)/RL/REC	0.090	RL	36	36	30	26	4	83.6	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-36X36X36(30+6)/RL/REC	0.090	RL	36	36	36	30	6	91.4	✓	–	✓	✓	–	✓	–	✓	✓
	CON-090-42X12X12(9.5+2.5)/HL/REC	0.090	HL	42	12	12	9.5	2.5	31.6	–	✓	–	–	–	✓	–	✓	✓
	CON-090-42X18X12(9.5+2.5)/HL/REC	0.090	HL	42	18	12	9.5	2.5	38.0	–	✓	–	–	–	✓	–	✓	✓
	CON-090-42X18X18(15.5+2.5)/HL/REC	0.090	HL	42	18	18	15.5	2.5	44.4	–	✓	–	–	–	✓	–	✓	✓
	CON-090-42X24X12(9.5+2.5)/HL/REC	0.090	HL	42	24	12	9.5	2.5	46.0	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X24X18(15.5+2.5)/HL/REC	0.090	HL	42	24	18	15.5	2.5	53.1	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X24X24(21.5+2.5)/HL/REC	0.090	HL	42	24	24	21.5	2.5	60.2	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X30X12(9.5+2.5)/HL/REC	0.090	HL	42	30	12	9.5	2.5	54.1	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X30X18(15.5+2.5)/HL/REC	0.090	HL	42	30	18	15.5	2.5	61.9	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X30X24(21.5+2.5)/HL/REC	0.090	HL	42	30	24	21.5	2.5	69.6	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X30X30(26+4)/RL/REC	0.090	RL	42	30	30	26	4	82.7	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X36X12(9.5+2.5)/HL/REC	0.090	HL	42	36	12	9.5	2.5	60.4	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X36X18(15.5+2.5)/HL/REC	0.090	HL	42	36	18	15.5	2.5	68.9	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X36X24(21.5+2.5)/HL/REC	0.090	HL	42	36	24	21.5	2.5	77.4	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X36X30(26+4)/RL/REC	0.090	RL	42	36	30	26	4	91.1	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X36X36(30+6)/RL/REC	0.090	RL	42	36	36	30	6	99.6	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X42X12(9.5+2.5)/HL/REC	0.090	HL	42	42	12	9.5	2.5	68.5	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X42X18(15.5+2.5)/HL/REC	0.090	HL	42	42	18	15.5	2.5	77.6	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X42X24(21.5+2.5)/HL/REC	0.090	HL	42	42	24	21.5	2.5	86.8	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X42X30(26+4)/RL/REC	0.090	RL	42	42	30	26	4	101.2	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X42X36(30+6)/RL/REC	0.090	RL	42	42	36	30	6	110.4	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-42X42X42(30+12)/RL/REC	0.090	RL	42	42	42	30	12	119.5	–	✓	✓	✓	–	✓	–	✓	✓
	CON-090-48X12X12(9.5+2.5)/HL/REC	0.090	HL	48	12	12	9.5	2.5	34.8	–	✓	–	–	✓	✓	–	✓	✓
	CON-090-48X18X12(9.5+2.5)/HL/REC	0.090	HL	48	18	12	9.5	2.5	41.7	–	✓	–	–	✓	✓	–	✓	✓
	CON-090-48X18X18(15.5+2.5)/HL/REC	0.090	HL	48	18	18	15.5	2.5	48.8	–	✓	✓	✓	✓	✓	–	✓	✓
	CON-090-48X24X12(9.5+2.5)/HL/REC	0.090	HL	48	24	12	9.5	2.5	50.4	–	✓	✓	✓	✓	✓	–	✓	✓
	CON-090-48X24X18(15.5+2.5)/HL/REC	0.090	HL	48	24	18	15.5	2.5	58.1	–	✓	✓	✓	✓	✓	–	✓	✓
	CON-090-48X24X24(21.5+2.5)/HL/REC	0.090	HL	48	24	24	21.5	2.5	65.9	–	✓	✓	✓	✓	✓	–	✓	✓
	CON-090-48X30X12(9.5+2.5)/HL/REC	0.090	HL	48	30	12	9.5	2.5	59.1	–	✓	✓	✓	✓	✓	–	✓	✓
	CON-090-48X30X18(15.5+2.5)/HL/REC	0.090	HL	48	30	18	15.5	2.5	67.5	–	✓	✓	✓	✓	✓	–	✓	✓
	CON-090-48X30X24(21.5+2.5)/HL/REC	0.090	HL	48	30	24	21.5	2.5	75.9	–	✓	✓	✓	✓	✓	–	✓	✓
	CON-090-48X30X30(26+4)/RL/REC	0.090	RL	48	30	30	26	4	89.6	–	✓	✓	✓	✓	✓	–	✓	✓

BASE PART NUMBER	SHELL THK (IN.)	LID STYLE	L (IN.)	W (IN.)	OVERALL H (IN.)	BASE D (IN.)	LID D (IN.)	APPROX. WT (LB)	RHW	RW	CA-F	CA-R	FL	LL	TD	HA	PH
CON-090-48X36X12(9.5+2.5)/HL/REC	0.090	HL	48	36	12	9.5	2.5	66.1	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X36X18(15.5+2.5)/HL/REC	0.090	HL	48	36	18	15.5	2.5	75.2	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X36X24(21.5+2.5)/HL/REC	0.090	HL	48	36	24	21.5	2.5	84.3	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X36X30(26+4)/RL/REC	0.090	RL	48	36	30	26	4	98.6	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X36X36(28+8)/RL/REC	0.090	RL	48	36	36	28	8	107.7	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X42X12(9.5+2.5)/HL/REC	0.090	HL	48	42	12	9.5	2.5	74.7	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X42X18(15.5+2.5)/HL/REC	0.090	HL	48	42	18	15.5	2.5	84.5	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X42X24(21.5+2.5)/HL/REC	0.090	HL	48	42	24	21.5	2.5	94.3	–	✓	✓	✓	✓	✓	–	✓	✓
CON-090-48X42X30(26+4)/RL/REC	0.090	RL	48	42	30	26	4	109.4	–	✓	✓	✓	✓	✓	–	✓	✓

RHW	Ret. Handle + Recessed Wheels	CA-R	Removable Casters	TD	Delta Lift / Tie-Down Rings
RW	STD Handle + Recessed Wheels	FL	Forklift Provisions / Skid Runners	HA	Extra Handles
CA-F	Fixed Swivel Casters	LL	Key-Lockable Recessed Latches	PH	Surface Mount Padlock Hasps